#### www.cet-power.com

## TSI BRAVO 60/230



### MODULAR INVERTER MODULE

POWER 2.5 kVA INPUT 60 Vdc and 230 Vac OUTPUT 230 Vac



#### DESCRIPTION

TSI Bravo – 60/230 is a compact modular inverter that converts **60 Vdc** power source into 230 Vac and provides a pure sine wave. By using at least three modules, we can offer solutions for **three-phase** infrastructures (3x400Vac + N).

The extra AC input ensures a **high overall efficiency** (up to 96%) which results in a reduction of energy loss and heat dissipation.

This module has a **modularity from 2.5 kVA to up to 80 kVA** in order to be able to evolve with your needs. The hot swap feature makes maintenance easier and reduces the risk of errors.

The low ripple voltage avoids any disturbances on DC loads and batteries.

#### **APPLICATIONS**

All business critical applications and all types of AC loads. The design is modular and scalable with hot- swappable inverter modules which ensures low Mean Time to Repair (MTTR), reduction in service costs and meets the changing needs for future expansion.

#### MAIN FEATURES

- >>> Extra AC input for increased efficiency
- >> Compact design
- >> Up to 80 kVA
- >>> No disturbances on DC loads & batteries



Illustrations are non-binding and may include customized fittin

Leading AC Backup Technology

#### www.cet-power.com

# >> TSI BRAVO

	TSI Bravo - 60 / 230
GENERAL	
Part number	T321740201
EMC (immunity)	EN 61000-4-2 / EN 61000-4-3 / EN 61000-4-4 / EN 61000-4-5 / EN 61000-4-6 / EN 61000-4-8
EMC (emission) (class)	EN 55022 (B)
Safety	EN62040-1
Cooling / Isolation	Forced / Doubled
MTBF	240 000 hrs (MIL-217-F)
Efficiency (Typical): Enhanced power conversion / on line	96% / 91%
Dielectric strength DC/AC	4300 Vdc
True Redundant Systems – compliant	3 disconnection levels on AC out and DC in power ports 4 disconnection levels on AC in port
RoHS	Compliant
Vibration	GR63 office vibration 0 to 100 hz-0.1 g / transport vibration 5-100 Hz 0.5 g 100 to 500 hz-1.5 g / Drop test
Operating conditions	Designed for installation in an IP20 or IP21 environment. When installed in a dusty or humid environment, appropriate measures (air filtering,) must be taken.
Altitude above sea without de-rating	< 1500 m / derating > 1500 m – 0.8 % per 100 m
Ambient / storage temperature / relative humidity	-20 to 50 ° C / -40 to 70 ° C / 95 %, non-condensing
Material (casing)	Coated steel-ALU ZINC
AC OUTPUT POWER	
Nominal Output power (VA) / (W)	2500 / 2000
Short time overload capacity	150 % (15 seconds) 110 % permanent within T° range
Admissible load power factor	Full power rating from 0 inductive to 0 capacitive
Internal temperature management and switch off	Yes
DC INPUT SPECIFICATIONS	
Nominal voltage (DC)	60 V
Voltage range (DC)	48 - 72 V
Nominal current	35 A (at 60 Vdc and 2000 W output)
Maximum input current (for 15 second) / voltage ripple	52 A < 100 mV rms
Input voltage boundaries	User selectable with T2S interface
AC INPUT SPECIFICATIONS	
Neminal voltage (AC)	200/220/240 V 1D or 2D (Min 2 shallos for 2D)
Voltage range (AC)	150 to 185 V linear derating 150 V//120 Watte par 10 V/ac
Brownout	2000 V/A /1600 W/ @ 150 V/cc
Conformity rongo before transfer to DC	
Dewer fector	Aujustable
Fower factor	> 9970 50 60 Hz / rongo 47 52 Hz / 57 62 Hz
	30 - 00 Hz / Talige 47 - 35 Hz / 37 - 03 Hz
	220/220/240 \/
Frequency / frequency accuracy	50 60 Hz / 0.02 %
Total harmonic distortion (resistive load)	<15%
	0.4 mg
Turn on delay	20 s to 40 s depending on the number of module installed
Nominal current Protected against reverse current	
Crest factor at nominal nower	10.3 A
With short aircuit management and protection	3 : 1
Short circuit clear up capacity	$10 \times I_n$ for 20 msec - Available while Mains is available at AC input port
	With magnitude control and management
Short circuit current after clear up capacity	2.1 $I_{\rm n}$ during 15 s and 1.5 $I_{\rm n}$ after 15 s
IN TRANSFER PERFORMANCE	
Max. voltage interruption / total transient voltage duration (max)	0 s / 0 s
SIGNALING & SUPERVISION	
Display	Synoptic LED
Alarms output / supervision	Dry contacts on shelf / Standard USB port and MODBUS on T2S, optional : Candis Display / Candis TCP-IP
Remote on / off	on rear terminal of the shelf via T2S

TSI Bravo - 60/230 - Datasheet v1.1 Specifications can change without notice. New data will be updated on our Web site: www.cet-power.com. The present equipment is protected by several international patents, trademarks and copyrights.



llustrations are non-binding and may include customized

Leading AC Backup Technology



\*Operation within lower voltage networks leads to de-rating of power performances.

